

Xsigo VP560 I/O Director™

SERVER INTERCONNECTS:	
Ports	24 non-blocking InfiniBand server ports
Interconnect	CX4 Copper (ports powered for fibre optic interfaces)
Speed	20 Gigabits per second per port full-duplex
EXPANSION SLOTS:	
Module Slots	4 slots for I/O and service modules 16 Gigabit per second full-duplex bandwidth per slot
10 GIGABIT ETHERNET I/O MODULE:	
Physical Ports	One optical XFP or Cx4 XFP Port
Virtual Interfaces	Up to 128 virtual NICs (vNICs) per module Up to 512 vNICs per VP560 IO Director
Quality of Service (QoS)	User-settable QoS features include: CIR – committed information rate PIR – peak information rate
PXE	Virtual NICs can be configured for PXE boot
MAC Addresses	Each vNIC is assigned a unique MAC address MAC addresses can dynamically migrate with specific virtual machine
Power Consumption	55 watts maximum
10-Port GIGABIT ETHERNET I/O MODULE:	
Physical Ports	10 gigabit Ethernet ports, RJ-45 style
Virtual Interfaces	Up to 160 Virtual NICs (vNICs) per module Up to 640 vNICs per VP560 I/O Director
Quality of Service (QoS)	User-settable QoS features include: CIR – committed information rate PIR – peak information rate
PXE	Virtual NICs can be configured for PXE boot
MAC Addresses	Each vNIC is assigned a unique MAC address MAC addresses can dynamically migrate with specific virtual machine
Power Consumption	55 watts maximum
4-GIGABIT FIBRE CHANNEL I/O MODULE:	
Physical Ports	Two 4/2/1 Gbps auto-negotiating SFP ports
Connectors	Two SFP optical transceivers (850nm)
Virtual Interfaces	Up to 128 virtual HBAs (vHBAs) per I/O module Up to 512 vHBAs per VP560 I/O Director (Two vHBAs reserved for internal card management)
Protocols	FC-AL, FCP (SCSI-FCP)
World Wide Name (WWN)	Each vHBA is assigned a unique WWN WWNs can dynamically migrate with specific virtual machine
Quality of Service	User settable QoS features include: CIR – Committed information rate PIR – Peak information rate
SAN Boot	Virtual HBAs can be configured for SAN Boot
Power Consumption	45 watts maximum
MANAGEMENT:	
Management Interfaces	Java-based management GUI, command-line interface (CLI) through SSH and Advanced API for integration with third party software
Lights Out Management	Supports IPMI based LOM
Management Module I/O	Ethernet management network, RS232 console, auxiliary ports, USB

Xsigo VP560 I/O Director™

REPLACEABLE PARTS:

Replaceable Modules I/O modules, management module, power supplies, fabric board, system controller, fan tray assemblies

HEAT DISSIPATION:

Base Chassis 300W or 1024 BTU
Loaded Chassis 650W or 2219 BTU
 Subject to system configuration

POWER:

Voltage 100 – 127 / 200 – 240 VAC
Max Current 10A @ 100 volts or 5.55A @ 180 volts
Frequency 50 - 60 Hz
Power Chassis (fully loaded): 650 watt maximum

ENVIRONMENTAL:

Operating Temp 5 degrees C to 35 degrees C
Relative Humidity 10 to 80% at 35 C, non-condensing
Non-operating Temp -40 degrees C to 70 degrees C
Non-operating Humidity 90% at 65 degrees C, non-condensing
Altitude (Operating) Up to 3000 m
Altitude (Non-operating) Up to 15,000 m

CHASSIS DIMENSIONS AND WEIGHT:

Height 2U - 88 mm (3.47 inches)
Width 444.5 mm (17.5 inches)
Depth 716 mm (28.2 inches)
Weight 22 kg (48 lb.) with no modules - modules are approximately 0.9 kg (2 lb.)

REGULATIONS:

Safety TUV 60950-1, CSA C22.2 No. 60950-1, EN 60950-1, IEC 60950-1
RFI/EMI FCC Class A, ICES Class A, VCCI Class A, EN 55022 Class A, CNS 13438 Class A, KN22 and KN24 Class A
Immunity EN5022:2006 including A1:2007, EN55024:1998 including A1:2001 and A2:2003, EN61000-3-2:2006, EN6100-3-3:1995
RoHS RoHS Level 5

MOUNTING SPECIFICATIONS:

Rack Mounting 19" universal EIA Rack, 2-post or 4-post mounting kit